Environmental Health Engineering and Management Journal. 2025;12:1403 http://ehemj.com

**Environmental Health Engineering and** MJ **Management Journal** 

Open Access

**Original** Article



CrossMark

## Removal of Aromatic Compounds by a Wet Packed-Bed Scrubber Filled with Waste Edible Oil

Saeed Motesaddi Zarandi<sup>10</sup>, Mohamadreza Massoudinejad<sup>10</sup>, Ali Atamaleki<sup>2</sup>, Reihaneh Janipoor<sup>3</sup>, Rajabali Hokmabadi<sup>4</sup>, Amir Mohammad Sheikh Asadi<sup>5</sup>, Elham Rahmanzadeh<sup>6</sup>, Mahdi Ghorbanian<sup>2,7</sup>,

<sup>1</sup>Department of Environmental Health Engineering, School of Public Health and Safety, Shahid Beheshti University of Medical Sciences, Tehran, Iran

<sup>2</sup>Department of Environmental Health Engineering, School of Public Health, North Khorasan University of Medical Sciences, Bojnurd, Iran

<sup>3</sup>Student Research Committee, School of Public Health and Safety, Shahid Beheshti University of Medical Sciences, Tehran, Iran <sup>4</sup>Department of Occupational Health Engineering, School of Public Health, North Khorasan University of Medical Sciences, Bojnurd, Iran <sup>5</sup>Chair of Environmental Analytics and Pollutants, Institute IWAR, Technical University of Darmstadt, Darmstadt, Germany

<sup>6</sup>Student Research Committee, School of Public Health, Iran University of Medical Sciences, Tehran, Iran

<sup>7</sup>Vector-Borne Diseases Research Center, North Khorasan University of Medical Sciences, Bojnurd, Iran

#### Abstract

Background: The emission of aromatic compounds, particularly BTEX (benzene, toluene, ethylbenzene, and xylene), into the atmosphere poses significant environmental and health issues. Recognizing the limitations of traditional water-based scrubbing methods for hydrophobic compounds, this study aimed to determine the optimal conditions for absorbing BTEX compounds released during the frying process, using waste edible oil as an innovative absorbent in a packed scrubber system.

Methods: The effects of operating parameters such as scrubber bed height, frequency of oil reuse, and pollutant contact time on the removal efficiency and absorption capacity of BTEX were investigated through laboratory-scale experiments and gas chromatography analysis.

Results: The results showed that the removal efficiency of BTEX significantly improved with increased bed height from 64 to 98% for B, from 56 to 87% for T, from 36 to 59% for E, and from 58 to 89% for X. The results also showed a significant decrease in removal efficiency during absorption time. However, the removal efficiencies did not change significantly for all chemicals among the waste oils. The removal efficiency of B related to the use of oil ranged from 80 to 90%, from 63 to 87% for T, from 19 to 58% for E, and from 65 to 88% for X.

Conclusion: This research demonstrates the potential of utilizing waste edible oils in packed scrubbers for effective BTEX removal, highlighting the importance of optimizing operational conditions for improved air pollution control. The findings contribute to the development of more sustainable and environmentally friendly solutions for mitigating VOCs.

Keywords: Benzene, Absorption, Volatile Organic Compound, Waste, BTEX

Citation: Motesaddi Zarandi S, Massoudinejad M, Atamaleki A, Janipoor R, Hokmabadi R, Sheikh Asadi AM, et al. Removal of aromatic compounds by a wet packed-bed scrubber filled with waste edible oil. Environmental Health Engineering and Management Journal. 2025;12:1403. doi: 10.34172/ EHEM.1403.

#### Introduction

Aromatic hydrocarbons, particularly benzene, toluene, ethylbenzene, and xylenes (BTEX), are significant pollutants emitted from various industrial and environmental processes. These chemicals have received extensive attention as they are precursors of toxic radicals in the atmosphere, leading to the formation of secondary pollutants through photochemical reactions, potentially endangering human health indirectly. They can also affect human health directly through inhalation and ingestion

routes (1,2). BTEX compounds are released into the environment through both natural and anthropogenic sources, contributing to environmental pollution. They can contaminate air, soil, and water, posing threats to human health and ecosystems (3-5). The U.S. Environmental Protection Agency (USEPA) classified BTEX as priority pollutants due to their toxic and carcinogenic properties. Even at low concentrations, they can cause damage to the kidneys and liver and paralyze the central nervous system (6,7). Various methods, including

© © 2025 The Author(s). Published by Kerman University of Medical Sciences. This is an open-access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/4.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Article History: Received: 3 August 2024 Revised: 3 December 2024 Accepted: 1 January 2025 ePublished: 20 July 2025

\*Correspondence to: Ali Atamaleki, Email: Aliatamaleki69@ vahoo.com; Mahdi Ghorbanian, Email: ghorbanian82@gmail. com



doi 10.34172/EHEM.1403

membrane separation, absorption, adsorption, catalytic oxidation, biodegradation, and combustion, have been studied to control VOCs (8,9). Gas-liquid mass transfer is a complex and important phenomenon frequently occurring in chemical operations, making gas scrubbing applicable for VOC removal (10). Reasonable removal efficiencies can be achieved using water as a scrubbing liquid when the target VOCs are hydrophilic, acidic, or basic (11). Water-packed columns operated at countercurrent are often chosen at the industrial scale, although co-current intensified gas-liquid contactors, such as aeroejectors, static mixers, and venturi scrubbers, could be used effectively (12).

However, many dangerous VOCs in different industrial processes, such as BTEX, are neutral and hydrophobic compounds. Therefore, the replacement of water with a non-aqueous phase liquid (NAPL) to efficiently remove these compounds has recently been reviewed (13). NAPL typically has viscosities one to three orders of magnitude higher than water, making it difficult to use co-current gas-liquid contactors and select a counter-current packed column. Despite the higher viscosity inducing greater mass transfer resistance, liquids with viscosities up to two orders of magnitude higher than water can be successfully implemented in packed columns (14-16).

Several researchers have investigated various synthetic NAPLs for VOC absorption at the laboratory scale, particularly silicone oils (17-19). Recently, Lhuissier et al. have evaluated the partition coefficients of several VOCs in four types of waste oils, indicating lower partition coefficients than those of silicone oils. They demonstrated that lubricants and transformer oils, with their low volatilities, are compatible with the absorption process (20). These waste oils might contain volatile compounds that could cause secondary emissions (21). Polyethylene glycols (PEG) are also investigated by Guo et al. as liquid phases for the absorption of VOCs (22). Ozturk and Yilmaz reported that absorption removal rates ranged from 70% to 95% for methanol, T, B, and carbon tetrachloride when using fresh and waste lubricants and vegetable oils (21). Malhautier et al. (23) investigated a mixture of aromatic, halogenated, and oxygenated compounds in soluble cutting oil. They found that the addition of oil enhanced the absorption of halogenated and aromatic compounds compared to water, but had the opposite effect for oxygenated compounds.

Only two experimental studies have reported T mass transfer in di-2-ethylhexyl adipate and silicone oil on a laboratory scale (24,25). In a previous study, Lhuissier et al. studied the hydrodynamics of lubricant and transformer waste oils in a lab-scale packed column filled with Flexipac<sup>®</sup> structured packing, demonstrating that it is possible to operate a counter-current packed column with viscous waste oils, particularly transformer oil (14). Margaux Lhuissier (2021) performed VOC absorption in a structured packing fed with waste oils, measuring removal efficiencies of hydrophobic VOCs in silicone and transformer oils up to 80-90%. Nonetheless, owing to its higher viscosity, the removal efficiencies of the lubricant were significantly lower (26).

However, limited investigations have been conducted on the absorption of VOCs, specifically BTEX, in waste oils using a packed column. Consequently, the primary objective of this research was to assess the absorption of BTEX compounds using a packed scrubber filled with waste edible oils.

### Materials and Methods

#### Chemicals

The analytical grade solutions of B, T, E, and X isomers were obtained in the highest purity available from Merck Co. (Darmstadt, Germany). A certain brand of blended cooking oil with the viscosity of 0.04 Pa.s and density of 943 kg/m<sup>3</sup> was chosen from the market as the absorbent for VOC removal.

#### Sampling and Analytical Methods

A gas-tight syringe (Hamilton Bonaduz, Switzerland) was used every five minutes (0–20 min) for sampling target compounds before and after the absorption column. The samples were measured using a Shimadzu-17A gas chromatograph equipped with a BP-5 (non-polar) capillary column (30 m in length, 0.32 mm in ID, and 0.32  $\mu$ m in film thickness), a split/splitless injection port, and a flame ionization detector (GC/FID). The programmed temperature was set at 40°C for 3 min, then increased to 140°C at the rate of 8°C min<sup>-1</sup>, and subsequently, raised to 230°C at a heating rate of 10°C min<sup>-1</sup>, maintaining this temperature for 5 min. The detector temperature was set at 300°C. The time for measuring the peak of target compounds was considered about 6, 8, 11, and 12 min for B, T, E, and X, respectively.

#### **Quality Control and Quality Assurance**

A calibrated rotameter was used to adjust and measure the gas flow. To obtain a calibration curve, specific concentrations of each target compound were prepared in a Tedlar Bag (SKC Inc., the USA) by calculating the designated volume of the liquid and volatilizing it into the sampling bag according to Eq. (1):

$$V = \frac{P \times V_{sb} \times C \times M_{w}}{\rho \times R \times T \times 1000} \tag{1}$$

Where V is the volume of the target compound ( $\mu$ L), P is the inside pressure of the sampling bag (atm),  $V_{sb}$  is the volume of the sampling bag (L), C is the BTEX concentration (ppmv), Mw is the molecular weight of BTEX (g/mol),  $\rho$  is the density of BTEX (g/mL), R is the universal gas constant (L atm/mol K), and T is the

temperature (K). The prepared concentrations (50–400 ppm) were injected into a GC/FID column, and a calibration curve was generated by plotting the BTEX concentrations against the area under the peak (21).

#### Laboratory Unit

A semi-packed scrubber filled with waste edible oil was used to absorb BTEX. The experimental setup of the laboratory unit is shown in Figure 1. BTEX compounds were separately injected into a carrier gas (with a flow rate of 200 mL/min) and, subsequently, volatilized (BTEX-N<sub>2</sub> mixture). The mean concentrations (ppm) for the BTEX compounds were  $89.87 \pm 8.62$ ,  $89.80 \pm 5.60$ ,  $87.53 \pm 13.00$ , and  $85.12 \pm 7.50$ , respectively. The volatilized compounds were introduced from the bottom of the absorption column and contacted with the thin film of waste edible oil covering the Raschig rings. In the next step, samples were taken from the top of the column and analyzed. Finally, the removal efficiency was calculated according to Eq. (2):

$$Eff, (\%) = \left(\frac{I-O}{I}\right) \times 100 \tag{2}$$



**Figure 1.** Scheme of the laboratory unit: (1) carrier gas, (2) agitation unit, (3) injection device, (4) absorption column, (5) oil storage chamber, (6) circulating pump, ( $\otimes$ ) sampling points

#### Table 1. Characteristics of the absorption unit

Where *I* and *O* are inlet and outlet concentrations, respectively. The characteristics of the absorption units are presented in Table 1.

#### Statistical analysis

Data analysis was conducted using IBM SPSS Statistics 16 software (IBM SPSS Inc., Armonk, NY, USA). The removal efficiencies of BTEX compounds are presented as mean $\pm$ standard deviation (SD). The normality of the data was evaluated using the Kolmogorov-Smirnov test, indicating that the efficiencies did not follow a normal distribution among the levels. Consequently, nonparametric methods were applied, and the Kruskal-Wallis test was used to compare the efficiencies across different heights and waste oils, with a significance level of 0.05.

#### Results

#### Absorption of BTEX Compounds from Oil by Scrubber

In this study, waste edible oil, a non-polar absorbent, was used to absorb non-polar organic compounds. According to the results, average B showed the highest removal efficiency, followed by X, T, and E.

# Effects of Operational Parameters on the Removal of BTEX Compounds

#### Bed Height

In the present study, we investigated the effect of bed height on the removal efficiency of BTEX compounds. The results indicated a direct correlation between bed height and pollutant removal rates. Moreover, the statistical test revealed a significant difference in efficiency among the heights for all target compounds except E. With a constant inlet flow rate, the EBCT values for bed heights of 15, 30, and 45 cm were 1.19, 2.38, and 3.57 minutes, respectively. As shown in Figure 2, B had the highest removal rate at a height of 15 cm, followed by X, T, and E. This order was consistent at bed heights of 30 cm and 45 cm. The findings indicate that column height significantly increases the removal efficiency of BTEX compounds.



#### Frequency of Oil Reuse

The effect of oil reuse (W1, W2, W3, W4) on target compound removal was innovatively investigated. Changes in the appearance of used oils are shown in Figure 3. The removal efficiency of the target compounds concerning the frequency of oil reuse is shown in Figure 4.

As shown in Figure 4, repeated use of the oil resulted in a slight decrease in efficiency for compounds X and B. In contrast, no clear pattern was observed for compounds T and E. According to the statistical test, the removal efficiencies did not change significantly for any of the chemicals among the waste oils. Generally, W1 exhibited the highest removal efficiency for all compounds. The order of removal was B>X>T>E for W1 and W2, X > B > T > E for W3, and B > T > X > E for W4. B showed the highest removal efficiency, while E showed the lowest. Based on the findings, W1 exhibited the highest removal efficiency, followed by W3, W4, and W2.

#### Contact Time

The removal efficiency of the target pollutants was measured over time (0, 5, 10, 15, and 20 minutes) by comparing the concentrations before and after the absorption unit. As shown in Figure 5, the total removal efficiencies ranged from 91.60% to 98.84% for B, 86.37% to 97.58% for T, 41.74% to 91.17% for E, and 76.96% to 94.78% for X over the observed periods.

The absorption efficiency of all pollutants decreased



Figure 2. The effect of the height of the absorption unit on the removal of BTEX compounds (W1, 20 min)



Figure 3. The appearance of the burnt oils used in the scrubbers

4



Figure 4. Effect of oil reuse frequency on the removal of BTEX compounds from the frying process (height 45 cm)



Figure 5. The removal efficiency of BTEX compounds from the frying process over time (W1, height 45 cm)

significantly over time, but at varying rates. According to the results, the highest slope was related to E, followed by X, T, and B. The absorption capacities for pollutants B, T, E, and X were calculated as 0.022, 0.020, 0.017, and 0.018 mg/g of absorbent, respectively.

#### Discussion

In the absorption process by the scrubber, three main parameters affect the efficiency: pollutant properties (concentration, solubility, chemical structure, and polarity), absorbent properties (flow rate, density, viscosity, chemical structure, polarity, and temperature), and scrubber design parameters (height, diameter, bed properties, and bed pore thickness) (21,27,28). The pollutant flow rate and concentration increase the speed of molecular movement, giving the absorbent less opportunity to contact them. Conversely, an increase in oil flow rate provides more opportunities for absorption due to its abundance. Therefore, theoretically, reducing the flow rate of the pollutant carrier gas or increasing the flow rate of the absorbent material enhances absorption efficiency (21,29).

However, practical increases in absorbent flow rate may not constantly significantly improve efficiency, depending on the chemical properties of the absorbing material. For instance, Chen et al. (29) found that the absorbent flow rate had little effect on  $NO_2$  removal by  $Na_2SO_3$  in a packed scrubber until the ratio of absorbent flow to gas flow increased by three times. Similarly, Chen et al. (30) investigated the effect of pollutant concentration, absorbent flow rate, and gas flow rate on  $CO_2$  removal by amines, identifying gas flow rate as the most influential parameter, followed by pollutant concentration and absorbent flow rate.

According to the principle of "like dissolves like," polar solutes dissolve in polar solvents and non-polar solutes in non-polar solvents (20,31). Shorter alkyl chain lengths can improve the absorption process, as demonstrated by studies showing higher diffusion of aromatic compounds in oil with shorter alkyl chains (32). Biard et al. (33) investigated VOC removal using a water-containing scrubber, finding poor efficiency due to the mixed hydrophilic and hydrophobic nature of VOC. Improved results were obtained using a scrubber with organic solvent in series with the water scrubber. Tarnpradab et al. (31) demonstrated high absorption rates for B, T, styrene, phenol, indene, and naphthalene using waste edible oil.

As mentioned earlier, B showed the highest removal efficiency, followed by X, T, and E. This order can be attributed to the compounds' physical and chemical properties (27). The higher absorption of B may be due to its lower molecular weight compared to the others (34). Additionally, volatility affects absorption, as low boiling temperature and high volatility can reduce absorption potential. Vuong et al. (34) have stated that three organic solvents, due to their low boiling temperatures and high volatilities, have a higher potential for absorbing dimethyl sulfide than T. This study demonstrated that the low boiling temperature and high volatility of dimethyl disulfide led to a reduction in absorption. Similarly, low ethanol absorption was attributed to its low boiling point and the presence of non-polar substances, like glycerol and glycol, in the absorbent (35). Despite high volatility reducing absorption, factors such as low molecular weight and polarity (non-polarity of the absorbent and absorbate) can mitigate this effect. Vegetable oils, containing glycerides with oxygen atoms, are not completely nonpolar and can remove compounds with low polarity (20, 27).

Scrubber design and related physical parameters can directly affect the efficiency (28). These parameters provide conditions for maximum contact surface and time between contaminated air and the absorbent. For example, Chiang et al. (36) used a rotary-packed scrubber to achieve maximum contact surface by creating a thin layer of oil on the packed media via centrifugal force. Their results showed a direct relationship between circulation speed and the removal efficiency of X and T. The effect of bed height on the removal efficiency of BTEX compounds was surveyed. The results indicated a direct correlation between bed height and pollutant removal rates. Specifically, increasing the bed height increased the contact time between the absorbent and the pollutant (33), which was calculated according to the EBCT values. Two parameters, inlet gas flow rate and column volume, affect the EBCT (37). With a constant inlet flow rate, the EBCT values for bed heights of 15, 30, and 45 cm were 1.19, 2.38, and 3.57 minutes, respectively.

Additionally, increasing the bed height can enhance the absorbent's holding capacity, reduce the column's crosssectional area, increase the collision rate between gas and liquid, and ultimately improve the mass transfer rate. A taller bed can also enhance mass transfer dynamics, facilitating better distribution and movement of chemicals toward the absorbent particles (38,39). Bhoi et al. (39) investigated the effects of various parameters, including solvent type (rapeseed and soybean oil), column height,

absorbent temperature, and absorbent flow rate, on the removal efficiency of compounds such as B, T, and E. The results showed that changes in column height (0.5, 0.8, and 1.1 meters) significantly impacted removal efficiency. Specifically, increasing the height from 0.5 to 1.1 meters improved B removal efficiency from 90% to 97%, although the increase was not significant for T and E. Liu et al. (40) measured the SO<sub>2</sub> absorption rate at different scrubber heights using H2O, NaHCO3, Na2CO3, Na2SO3, and NaHSO<sub>3</sub> absorbents. They observed that the absorption rate increased with height up to a certain point, then stabilized at heights between 2.5 and 3 meters, which they attributed to absorbent saturation. Dashliborun et al. (38) examined the effect of packing type (M500X and Raschig rings), perpendicular angle (0, 5, 10, and 15 degrees), and column height (0.45 and 0.9 meters) on CO<sub>2</sub> removal using amine. They found that increasing the height at a zero-degree angle improved scrubber efficiency from 75% to 87% with the Raschig ring pack. Liu et al. (40) measured the SO<sub>2</sub> absorption rate at different scrubber heights using H<sub>2</sub>O, NaHCO<sub>3</sub>, Na<sub>2</sub>CO<sub>3</sub>, Na<sub>2</sub>SO<sub>3</sub>, and NaHSO<sub>3</sub> absorbents. They observed that the absorption rate increased with height up to a point, stabilizing at heights between 2.5 and 3 meters, which they attributed to absorbent saturation.

The effect of oil reuse (W1, W2, W3, W4) on the removal of the target compound was investigated. Waste edible oil exhibits hydrophobic characteristics and possesses a distinctive composition of fatty acids and triglycerides. This attribute may facilitate the solubility of specific aromatic compounds, thereby enhancing their absorption (41). Considering that the oil used in the first phase of the study had been reused multiple times, it is expected that it had changed its chemical properties and accumulated impurities (20,42-44), leading to changes in its appearance (Figure 3). Based on the findings, the removal efficiencies did not change significantly for any of the chemicals among the waste oils. W1 exhibited the highest removal efficiency, followed by W3, W4, and W2. The higher removal efficiency of W1 may be attributed to chemical reactions such as oxidation and hydrogenation that occur during heating (45). Additionally, the presence of food ingredients in the oil can lead to the formation of other pollutants, which can affect absorption efficiency (21). W2, W3, and W4 removed lower concentrations. Generally, oil burning increases the viscosity of the fluid and changes its color. Viscosity is considered an influential parameter for absorption. Higher viscosity prevents the formation of smaller droplets, resulting in weaker diffusion of volatile organic compounds in the oil (27,35,46). Therefore, the most probable reason for the decreased efficiency is the increased viscosity caused by heating, which is associated with chemical changes in the oil (21). In a study (45), the authors compared the T-removal efficiency of sunflower oil with high oleic acid content to that of commercial sunflower oil. The findings

indicated that the removal efficiencies of both oils were comparable and not statistically different. This could be attributed to opposing factors: sunflower oil's low resistance to oxidation due to its high oleic acid content, and its high Henry's law constant for T absorption. However, the lower resistance of the oil to oxidation (3.5 times less) results in chemical modifications, reducing its absorption capacity. On the other hand, the higher Henry's law constant of this oil compared to commercial oil allows it to absorb more T.

Changing the absorbent phase from organic to inorganic, and vice versa, alters the rate of pollutant transfer from the gaseous to the liquid phase. Lalanne et al. (29) used a semi-industrial bioscrubber containing different percentages of oil and water to remove three groups of volatile organic compounds, including aromatic, oxygenated, and halogenated compounds. Their results showed that increasing the percentage of oil relative to water increased the efficiency of aromatic compound removal, resulting in faster saturation of the absorbent over time.

The absorption capacity and removal pattern of target chemicals over 20 minutes were considered. According to the results, E had the highest slope attributed to the lower capacity, followed by X, T, and B. The difference can be due to factors such as mass transfer, reaction kinetics, and the characteristics of the sorbate (47). Nakamura et al. (48) studied the absorption of tar by organic oil for 22.5 hours, finding removal efficiencies ranging from 60% to 70%, indicating a lower tendency of the absorbent material due to the presence of various pollutants. In another study (21), the absorption efficiencies of waste vegetable oil for removing compounds B and T were compared. The results indicated that the absorption efficiency for B at 400 minutes and T at 700 minutes was below 10%, showing a higher removal capacity of the oil. Tarnpradab et al. (31) observed a similar pattern after comparing the absorption of B and T by waste edible oil over 600 minutes. However, in the study by Bhoi et al. (49), the absorption of B, T, and E in soybean oil at a temperature of 50°C showed a different order, with E having the lowest slope (highest absorption efficiency), followed by T and B. This difference can be attributed to the volatility of the compounds. Another probable reason is the chemical properties of soybean oil, which contains high levels of glyceride compounds.

#### Conclusion

This study investigated the potential of waste edible oil for removing BTEX compounds in packed scrubbers. The key findings reveal that the high absorption efficiency of waste edible oil, particularly for B, can be attributed to its non-polarity and compatibility with non-polar BTEX compounds. Additionally, the study highlights the significance of bed height in the packed scrubber system, indicating that increasing the height enhances

the removal efficiency of BTEX components for a longer contact time and improves mass transfer. Furthermore, heated oils, especially W1, were found to play a significant role in removal efficiency, suggesting that the properties of the oil and the frequency of its usage affect absorption. The observations regarding the progressive decrease in absorption efficiency over time emphasize the need for periodic replacement or regeneration of the absorbent to maintain the effectiveness of the scrubber system. In conclusion, the research supports the argument that waste edible oil can be an effective absorbent for BTEX compounds, offering a novel approach to addressing environmental pollution. Further optimization of scrubber design parameters, such as bed height and oil reuse strategies, could enhance the economic and ecological benefits of this technology. The study advocates for broader adoption and continuous improvement of waste edible oil absorption systems for the remediation of harmful industrial emissions, contributing to cleaner air and a healthier environment.

#### Acknowledgements

The completion of this research project would not have been possible without the contributions and support of the Shahid Beheshti University of Medical Sciences. The authors are deeply grateful for the financial support provided by the Shahid Beheshti University of Medical Sciences, Iran.

#### Authors' contributions

Conceptualization: Ali Atamaleki. Data curation: Saeed Motesaddi Zarandi, Mohamadreza Massoudinejad. Formal analysis: Ali Atamaleki. Investigation: Ali Atamaleki. Methodology: Ali Atamaleki, Saeed Motesaddi Zarandi, Mohamadreza Massoudinejad. Project administration: Saeed Motesaddi Zarandi. Software: Ali Atamaleki. Supervision: Mahdi Ghorbanian. Validation: Mahdi Ghorbanian, Elham Rahmanzadeh. Visualization: Reihaneh Janipour, Rajabali Hokmabadi. Writing-original draft: Reihaneh Janipour, Rajabali Hokmabadi, Mahdi Ghorbanian. Writing-review & editing: Mahdi Ghorbanian, Amir Mohammad Sheikh Asadi.

#### **Competing interests**

The authors declare that they have no conflict of interest regarding the publication of this paper. The authors have not received any financial support or benefits from any organization or individual that could influence the research or the results. Additionally, the authors declare that they have not been involved in any activities or relationships that could create a potential conflict of interest with the subject matter or materials discussed in this paper.

#### **Ethical issues**

The project study mentioned in this article has undergone ethical evaluation at Shahid Beheshti University of Medical Sciences (Ethical code: IR.SBMU.PHNS.REC.1399.150). The authors confirm their agreement for the publication of this article.

#### Funding

Shahid Beheshti University of Medical Sciences founded this study.

#### References

- 1. Farzadkia M, Kermani M, Esarfili A, Ghorbanian M, Borhani Yazdi N, Abouee Mehrizi E. Studying removal of PHCs from deposits of petroleum storage tanks by ozonation method: determining optimal conditions by central composite design method. J Environ Health Sustain Dev. 2022;7(1):1571-82. doi: 10.18502/jehsd.v7i1.8967.
- Atamaleki A, Motesaddi Zarandi S, Massoudinejad M, Samimi K, Fakhri Y, Ghorbanian M, et al. The effect of frying process on the emission of the volatile organic compounds and monocyclic aromatic group (BTEX). Int J Environ Anal Chem. 2023;103(18):6169-82. doi: 10.1080/03067319.2021.1950148.
- Rahman S, Al-Gawati MA, Alfaifi FS, Alenazi WK, Alarifi N, Albrithen H, et al. Detection of aromatic hydrocarbons in aqueous solutions using quartz tuning fork sensors modified with calix[4]arene methoxy ester self-assembled monolayers: experimental and density functional theory study. Molecules. 2023;28(19):6808. doi: 10.3390/ molecules28196808.
- Hosseini S, Azadi D, Absalan A. First isolation of biodegradable polycyclic aromatic hydrocarbons *Mycobacterium porcinum* and *Mycobacterium celeriflavum* from oil-polluted ecosystems. Environ Health Eng Manag. 2022;9(2):97-104. doi: 10.34172/ehem.2022.11.
- Feizi R, Jorfi S, Takdastan A. Bioremediation of phenanthrene-polluted soil using *Bacillus kochii* AHV-KH14 as a halo-tolerant strain isolated from compost. Environ Health Eng Manag. 2020;7(1):23-30. doi: 10.34172/ ehem.2020.04.
- Jo MS, Rene ER, Kim SH, Park HS. An analysis of synergistic and antagonistic behavior during BTEX removal in batch system using response surface methodology. J Hazard Mater. 2008;152(3):1276-84. doi: 10.1016/j. jhazmat.2007.08.002.
- Rene ER, Mohammad BT, Veiga MC, Kennes C. Biodegradation of BTEX in a fungal biofilter: influence of operational parameters, effect of shock-loads and substrate stratification. Bioresour Technol. 2012;116:204-13. doi: 10.1016/j.biortech.2011.12.006.
- Zhu L, Shen D, Luo KH. A critical review on VOCs adsorption by different porous materials: species, mechanisms and modification methods. J Hazard Mater. 2020;389:122102. doi: 10.1016/j.jhazmat.2020.122102.
- 9. Atamaleki A, Motesaddi Zarandi S, Massoudinejad M, Hesam G, Naimi N, Esrafili A, et al. Emission of aldehydes from different cooking processes: a review study. Air Qual

Atmos Health. 2022;15(7):1183-204. doi: 10.1007/s11869-021-01120-9.

- Khan FI, Ghoshal AK. Removal of volatile organic compounds from polluted air. J Loss Prev Process Ind. 2000;13(6):527-45. doi: 10.1016/s0950-4230(00)00007-3.
- 11. Biard PF, Couvert A. Overview of mass transfer enhancement factor determination for acidic and basic compounds absorption in water. Chem Eng J. 2013;222:444-53. doi: 10.1016/j.cej.2013.02.071.
- Biard PF, Couvert A, Renner C. Intensification of volatile organic compound absorption in a compact wet scrubber at co-current flow. Chemosphere. 2017;173:612-21. doi: 10.1016/j.chemosphere.2017.01.075.
- Bruneel J, Walgraeve C, Dumortier S, Stockman J, Demeyer P, Van Langenhove H. Increasing mass transfer of volatile organic compounds in air scrubbers: a fundamental study for different gas-liquid systems. J Chem Technol Biotechnol. 2018;93(5):1468-76. doi: 10.1002/jctb.5515.
- 14. Lhuissier M, Couvert A, Kane A, Amrane A, Audic JL, Biard PF. Experimental evaluation and modeling of the hydrodynamics in structured packing operated with viscous waste oils. Chem Eng Res Des. 2020;162:273-83. doi: 10.1016/j.cherd.2020.07.031.
- Song D, Seibert AF, Rochelle GT. Mass transfer parameters for packings: effect of viscosity. Ind Eng Chem Res. 2018;57(2):718-29. doi: 10.1021/acs.iecr.7b04396.
- Song D, Seibert AF, Rochelle GT. Effect of liquid viscosity on the liquid phase mass transfer coefficient of packing. Energy Procedia. 2014;63:1268-86. doi: 10.1016/j. egypro.2014.11.136.
- 17. Patel MJ, Popat SC, Deshusses MA. Determination and correlation of the partition coefficients of 48 volatile organic and environmentally relevant compounds between air and silicone oil. Chem Eng J. 2017;310:72-8. doi: 10.1016/j.cej.2016.10.086.
- Guillerm M, Couvert A, Amrane A, Dumont É, Norrant E, Lesage N, et al. Characterization and selection of PDMS solvents for the absorption and biodegradation of hydrophobic VOCs. J Chem Technol Biotechnol. 2016;91(6):1923-7. doi: 10.1002/jctb.4792.
- 19. Tatin R, Moura L, Dietrich N, Baig S, Hébrard G. Physical absorption of volatile organic compounds by spraying emulsion in a spray tower: experiments and modelling. Chem Eng Res Des. 2015;104:409-15. doi: 10.1016/j. cherd.2015.08.030.
- Lhuissier M, Couvert A, Amrane A, Kane A, Audic JL. Characterization and selection of waste oils for the absorption and biodegradation of VOC of different hydrophobicities. Chem Eng Res Des. 2018;138:482-9. doi: 10.1016/j.cherd.2018.08.028.
- Ozturk B, Yilmaz D. Absorptive removal of volatile organic compounds from flue gas streams. Process Saf Environ Prot. 2006;84(5):391-8. doi: 10.1205/psep05003.
- 22. Guo X, Yao W, Chen Y, Fan J, Zhao Y, Wang J. PEGfunctionalized ionic liquids: a class of liquid materials for highly efficient extraction of rare earth metals from aqueous solutions. J Mol Liq. 2017;236:308-13. doi: 10.1016/j.molliq.2017.04.044.
- 23. Malhautier L, Lalanne F, Fanlo JL. Bioscrubbing as a treatment for a complex mixture of volatile organic compounds: influence of the absorption column characteristics on performance. Can J Civ Eng. 2009;36(12):1926-34. doi: 10.1139/l09-107.

- Guillerm M, Couvert A, Amrane A, Norrant E, Lesage N, Dumont É. Absorption of toluene in silicone oil: effect of the solvent viscosity on hydrodynamics and mass transfer. Chem Eng Res Des. 2016;109:32-40. doi: 10.1016/j. cherd.2015.12.028.
- Heymes F, Demoustier PM, Charbit F, Fanlo JL, Moulin P. Hydrodynamics and mass transfer in a packed column: case of toluene absorption with a viscous absorbent. Chem Eng Sci. 2006;61(15):5094-106. doi: 10.1016/j.ces.2006.03.037.
- 26. Lhuissier M, Couvert A, Kane A, Amrane A, Audic JL, Biard PF. Volatile organic compounds absorption in a structured packing fed with waste oils: experimental and modeling assessments. Chem Eng Sci. 2021;238:116598. doi: 10.1016/j.ces.2021.116598.
- Ozturk B, Kuru C, Aykac H, Kaya S. VOC separation using immobilized liquid membranes impregnated with oils. Sep Purif Technol. 2015;153:1-6. doi: 10.1016/j. seppur.2015.08.032.
- Lalanne F, Malhautier L, Roux JC, Fanlo JL. Absorption of a mixture of volatile organic compounds (VOCs) in aqueous solutions of soluble cutting oil. Bioresour Technol. 2008;99(6):1699-707. doi: 10.1016/j.biortech.2007.04.006.
- Chen L, Lin JW, Yang CL. Absorption of NO2 in a packed tower with Na2SO3 aqueous solution. Environ Prog. 2002;21(4):225-30. doi: 10.1002/ep.670210411.
- Chen PC, Yang MW, Wei CH, Lin SZ. Selection of blended amine for CO2 capture in a packed bed scrubber using the Taguchi method. Int J Greenh Gas Control. 2016;45:245-52. doi: 10.1016/j.ijggc.2015.11.017.
- Tarnpradab T, Unyaphan S, Takahashi F, Yoshikawa K. Tar removal capacity of waste cooking oil absorption and waste char adsorption for rice husk gasification. Biofuels. 2016;7(4):401-12. doi: 10.1080/17597269.2016.1147919.
- Matsumoto M, Inomoto Y, Kondo K. Selective separation of aromatic hydrocarbons through supported liquid membranes based on ionic liquids. J Memb Sci. 2005;246(1):77-81. doi: 10.1016/j.memsci.2004.08.013.
- Biard PF, Couvert A, Giraudet S. Volatile organic compounds absorption in packed column: theoretical assessment of water, DEHA and PDMS 50 as absorbents. J Ind Eng Chem. 2018;59:70-8. doi: 10.1016/j. jiec.2017.10.008.
- Vuong MD, Couvert A, Couriol C, Amrane A, Le Cloirec P, Renner C. Determination of the Henry's constant and the mass transfer rate of VOCs in solvents. Chem Eng J. 2009;150(2-3):426-30. doi: 10.1016/j.cej.2009.01.027.
- Cardoso VM, Bernardo A, Giulietti M. Ethanol absorption from CO2 using solutions of glycerol and glycols. Chem Eng Commun. 2018;205(10):1507-19. doi: 10.1080/00986445.2018.1458027.
- Chiang CY, Liu YY, Chen YS, Liu HS. Absorption of hydrophobic volatile organic compounds by a rotating packed bed. Ind Eng Chem Res. 2012;51(27):9441-5. doi: 10.1021/ie2021637.

- Yang C, Suidan MT, Zhu X, Kim BJ, Zeng G. Effect of gas empty bed contact time on performances of various types of rotating drum biofilters for removal of VOCs. Water Res. 2008;42(14):3641-50. doi: 10.1016/j.watres.2008.05.012.
- Motamed Dashliborun A, Larachi F, Taghavi SM. Gasliquid mass-transfer behavior of packed-bed scrubbers for floating/offshore CO2 capture. Chem Eng J. 2019;377:119236. doi: 10.1016/j.cej.2018.06.025.
- Bhoi PR, Huhnke RL, Kumar A, Payton ME, Patil KN, Whiteley JR. Vegetable oil as a solvent for removing producer gas tar compounds. Fuel Process Technol. 2015;133:97-104. doi: 10.1016/j.fuproc.2014.12.046.
- 40. Liu D, Xiong Z, Jin J, Wall T, Stanger R. Conceptual design of a packed bed for the removal of SO2 in oxy-fuel combustion prior to compression. Int J Greenh Gas Control. 2016;53:65-78. doi: 10.1016/j.ijggc.2016.07.031.
- Liang CY, Hsu PT, Yuan MH, Chen YH, Chang CM, Chang CY, et al. Removal of fine particulate matter from cookingoil fume using an intensified mobile chemical scrubber based on a rotating packed bed with green surfactants. Process Saf Environ Prot. 2022;164:669-77. doi: 10.1016/j. psep.2022.06.054.
- Domínguez R, Gómez M, Fonseca S, Lorenzo JM. Effect of different cooking methods on lipid oxidation and formation of volatile compounds in foal meat. Meat Sci. 2014;97(2):223-30. doi: 10.1016/j.meatsci.2014.01.023.
- Frankel E. Lipid Oxidation. Dundee, Scotland: The Oily Press Ltd; 1998.
- Saldanha T, Bragagnolo N. Relation between types of packaging, frozen storage and grilling on cholesterol and fatty acids oxidation in Atlantic hake fillets (*Merluccius hubbsi*). Food Chem. 2008;106(2):619-27. doi: 10.1016/j. foodchem.2007.06.021.
- 45. Hariz R, del Rio Sanz JI, Mercier C, Valentin R, Dietrich N, Mouloungui Z, et al. Absorption of toluene by vegetable oil–water emulsion in scrubbing tower: experiments and modeling. Chem Eng Sci. 2017;157:264-71. doi: 10.1016/j. ces.2016.06.008.
- Dietrich N, Mayoufi N, Poncin S, Li HZ. Experimental investigation of bubble and drop formation at submerged orifices. Chem Pap. 2013;67(3):313-25. doi: 10.2478/ s11696-012-0277-5.
- 47. Abdulwahid AA. Heat and Mass Transfer Mechanisms in a Wet Scrubber [dissertation]. James Cook University; 2020.
- Nakamura S, Kitano S, Yoshikawa K. Biomass gasification process with the tar removal technologies utilizing bio-oil scrubber and char bed. Appl Energy. 2016;170:186-92. doi: 10.1016/j.apenergy.2016.02.113.
- 49. Bhoi PR, Huhnke RL, Whiteley JR, Gebreyohannes S, Kumar A. Equilibrium stage-based model of a vegetable oil based wet packed bed scrubbing system for removing producer gas tar compounds. Sep Purif Technol. 2015;142:196-202. doi: 10.1016/j.seppur.2014.12.044.